

## SECTION 1: Product identifier

### 1.1. Product identifier

Product form : Mixture  
Trade name : 337  
Product code : 337

### 1.2. Recommended uses and restrictions

Relevant identified uses : Test gas/Calibration gas. Laboratory use.

### 1.3. Supplier information

CAC GAS & Instrumentation Pty Ltd

Unit 3 36 Holbeche Rd

2148 Arndell Park - AUSTRALIA

T +61 2 8676 6500

[cac@cacgas.com.au](mailto:cac@cacgas.com.au) - <http://www.cacgas.com.au/>

Emergency telephone number: 02 8676 6500

## SECTION 2: Hazards identification

### 2.1. Classification of the hazardous chemical

#### Classification (GHS AU)

Press. Gas (Comp.) H280

### 2.2. Label elements

Hazard pictograms (GHS AU) :



Hazard pictograms (GHS AU) :

GHS04

Signal word (GHS AU) :

Warning

Hazard statements (GHS AU) :

H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (GHS AU) :

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

### 2.3. Other hazards

Other hazards which do not result in classification

: None.

## SECTION 3: Composition/information on ingredients

Name	CAS-No.	Compound type	%	Classification according to the United Nations GHS (Rev. 4, 2011)
Nitrogen	7727-37-9		68	Press. Gas (Comp.), H280
oxygen	7782-44-7		1 – 21	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Carbon dioxide	124-38-9		0.0001 – 10	Press. Gas (Liq.), H280

Name	CAS-No.	Compound type	%	Classification according to the United Nations GHS (Rev. 4, 2011)
pentane	109-66-0		≤ 0.7	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411
carbon monoxide	630-08-0		0.0001 – 0.25	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Repr. 1A, H360 Acute Tox. 3 (Inhalation: gases), H331 STOT RE 1, H372
hydrogen sulphide	7783-06-4		0.0001 – 0.05	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Acute Tox. 2 (Inhalation: gases), H330 Aquatic Acute 1, H400

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
First-aid measures after skin contact	: Adverse effects not expected from this product. Wash skin with plenty of water.
First-aid measures after eye contact	: Adverse effects not expected from this product. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Ingestion is not considered a potential route of exposure. Call a poison center or a doctor if you feel unwell.

### 4.2. Symptoms caused by exposure

Most important symptoms and effects, both acute and delayed	: See section 11.
---	-------------------

### 4.3. Indication of any immediate medical attention and special treatment needed

Other medical advice or treatment	: None.
-----------------------------------	---------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray or fog. Water spray. Dry powder. Foam.
Unsuitable extinguishing media	: Do not use water jet to extinguish.

### 5.2. Special hazards arising from the substance or mixture

General measures	: Try to stop release. Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Act in accordance with local emergency plan. Stay upwind.
Hazardous combustion products	: Incomplete combustion may form carbon monoxide.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Special protective equipment for fire fighters	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.
------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Try to stop release. Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Act in accordance with local emergency plan. Stay upwind.
------------------	---

#### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area.
----------------------	----------------------------

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

### 6.2. Environmental precautions

Avoid release to the environment. Try to stop release.

### 6.3. Methods and material for containment and cleaning up

Methods and material for containment and cleaning up	: Ventilate area.
--	-------------------

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Safe handling of the gas receptacle	: Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.
Safe use of the product	: The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Do not smoke while handling product. Avoid exposure, obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Use only oxygen approved lubricants and oxygen approved sealings. Avoid suck back of water, acid and alkalis. Do not breathe gas. Avoid release of product into work area.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Protect from sunlight. Store in a well-ventilated place. Keep cool.
Conditions for safe storage, including any incompatibilities	: Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters - exposure standards

# 337

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

<b>hydrogen sulphide (7783-06-4)</b>		
USA - ACGIH	Local name	Hydrogen sulfide
USA - ACGIH	ACGIH OEL TWA [ppm]	1 ppm
USA - ACGIH	ACGIH OEL STEL [ppm]	5 ppm
USA - ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; CNS impair
<b>carbon monoxide (630-08-0)</b>		
USA - ACGIH	Local name	Carbon monoxide
USA - ACGIH	ACGIH OEL TWA [ppm]	25 ppm
USA - ACGIH	Remark (ACGIH)	TLV® Basis: COHb-emia. Notations: BEI
<b>Carbon dioxide (124-38-9)</b>		
USA - ACGIH	Local name	Carbon dioxide
USA - ACGIH	ACGIH OEL TWA [ppm]	5000 ppm
USA - ACGIH	ACGIH OEL STEL [ppm]	30000 ppm
USA - ACGIH	Remark (ACGIH)	TLV® Basis: Asphyxia
<b>Nitrogen (7727-37-9)</b>		
USA - ACGIH	Local name	Nitrogen
USA - ACGIH	Remark (ACGIH)	TLV® Basis: Simple Asphyxiant
<b>pentane (109-66-0)</b>		
Australia	Local name	Pentane
Australia	OES TWA [1]	1770 mg/m <sup>3</sup>
Australia	OES TWA [2]	600 ppm
Australia	OES STEL	2210 mg/m <sup>3</sup>
Australia	OES STEL [ppm]	750 ppm
USA - ACGIH	Local name	Pentane
USA - ACGIH	ACGIH OEL TWA [ppm]	1000 ppm
USA - ACGIH	Remark (ACGIH)	TLV® Basis: Narcosis; resp tract irr
China	Local name	戊烷 (全部异构体) # Pentane (all isomers)
China	OEL PC-TWA	500 mg/m <sup>3</sup>
China	OEL PC-STEL	1000 mg/m <sup>3</sup>
New Zealand	Local name	Pentane
New Zealand	WES-TWA (OEL TWA) [1]	1770 mg/m <sup>3</sup>
New Zealand	WES-TWA (OEL TWA) [2]	600 ppm
New Zealand	WES-STEL (OEL STEL)	2120 mg/m <sup>3</sup>
New Zealand	WES-STEL (OEL STEL) [ppm]	750 ppm

### Exposure limit values for the other components

No additional information available

### 8.2. Monitoring

No additional information available

### 8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Product to be handled in a closed system and under strictly controlled conditions. Provide adequate general and local exhaust ventilation. Preferably use permanent leak-tight installations (e.g. welded pipes). Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits (where available). Consider the use of a work permit system e.g. for maintenance activities.

### 8.4. Personal protective equipment

Personal protective equipment : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.

# 337

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Hand protection	: Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk.
Eye protection	: Safety glasses. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known. Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers. Consult respiratory device supplier's product information for the selection of the appropriate device. Gas filters do not protect against oxygen deficiency. Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks . Keep self contained breathing apparatus readily available for emergency use. Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Thermal hazard protection	: None in addition to the above sections.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. Avoid release to the environment.
Other information	: Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.



### 9.1. SECTION 9: Physical and chemical properties

Physical state	: Gas
Appearance	:
Molecular mass	: Not applicable for gas mixtures.
Colour	: Mixture contains one or more component(s) which have the following colour(s): Colourless.
Odour	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Rotten eggs.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
pH	: Not applicable for gases and gas mixtures.
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable for gases and gas mixtures.
Melting point / Freezing point	: Melting point : Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
Flammability (solid, gas)	: No data available
Vapour pressure	: Vapour pressure : Not applicable. Vapour pressure at 50 °C : Not applicable.
Relative density	: Relative vapour density at 20 °C : Not applicable. Relative gas density : Lighter or similar to air.
Density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: Not applicable for gas mixtures.
Viscosity	: Viscosity, kinematic : Not applicable. Viscosity, dynamic : Not applicable.
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
Explosive limits	: Non flammable.
Minimum ignition energy	: No data available

# 337

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Fat solubility	: No data available
Additional information	: None.

### 10.1. SECTION 10: Stability and reactivity

Reactivity	: No reactivity hazard other than the effects described in sub-sections below.No reactivity hazard other than the effects described in sub-sections below.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid moisture in installation systems.
Incompatible materials	: For additional information on compatibility refer to ISO 11114.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### 11.1. SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### hydrogen sulphide (7783-06-4)

LC50 Inhalation - Rat [ppm]	356 ppm/4h
-----------------------------	------------

#### carbon monoxide (630-08-0)

LC50 Inhalation - Rat [ppm]	3760 ppm/1h (ADR)
-----------------------------	-------------------

Skin corrosion/irritation	: Not classified pH: Not applicable for gases and gas mixtures.
Serious eye damage/irritation	: Not classified pH: Not applicable for gases and gas mixtures.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

#### 337

Viscosity, kinematic	Not applicable.
Viscosity, dynamic	Not applicable.
Viscosity, kinematic	Not applicable.

### SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

#### 12.1. Ecotoxicity

Ecology - general	: Classification criteria are not met.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

#### 337

Partition coefficient n-octanol/water (Log Kow)	Not applicable for gas mixtures.
Partition coefficient n-octanol/water (Log Pow)	Not applicable for gas mixtures.

#### hydrogen sulphide (7783-06-4)

LC50 96 h - Fish [mg/l]	0.007 – 0.019 mg/l
EC50 48h - Daphnia magna [mg/l]	0.12 mg/l
EC50 72h - Algae [mg/l]	1.87 mg/l
Partition coefficient n-octanol/water (Log Pow)	Not applicable for inorganic products.

#### carbon monoxide (630-08-0)

Partition coefficient n-octanol/water (Log Pow)	1.78
---	------

# 337

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

<b>Carbon dioxide (124-38-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.83
<b>oxygen (7782-44-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	Not applicable for inorganic products.
<b>Nitrogen (7727-37-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	Not applicable for inorganic products.

### 12.2. Persistence and degradability

<b>337</b>	
Persistence and degradability	No data available.
<b>hydrogen sulphide (7783-06-4)</b>	
Persistence and degradability	Not applicable for inorganic products.
<b>carbon monoxide (630-08-0)</b>	
Persistence and degradability	Will not undergo hydrolysis. Not readily biodegradable.
<b>Carbon dioxide (124-38-9)</b>	
Persistence and degradability	No ecological damage caused by this product.
<b>oxygen (7782-44-7)</b>	
Persistence and degradability	No ecological damage caused by this product.
<b>Nitrogen (7727-37-9)</b>	
Persistence and degradability	No ecological damage caused by this product.

### 12.3. Bioaccumulative potential

<b>337</b>	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Partition coefficient n-octanol/water (Log Kow)	See section 12.1 on ecotoxicology
Bioaccumulative potential	No data available.
<b>hydrogen sulphide (7783-06-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Bioaccumulative potential	No data available.
<b>carbon monoxide (630-08-0)</b>	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). See section 9.
<b>Carbon dioxide (124-38-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Bioaccumulative potential	No ecological damage caused by this product. Not expected to bioaccumulate due to the low log Kow (log Kow < 4). See section 9.
<b>oxygen (7782-44-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Bioaccumulative potential	No ecological damage caused by this product.
<b>Nitrogen (7727-37-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Bioaccumulative potential	No ecological damage caused by this product.

### 12.4. Mobility in soil

<b>337</b>	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
<b>hydrogen sulphide (7783-06-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
<b>carbon monoxide (630-08-0)</b>	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
<b>Carbon dioxide (124-38-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Ecology - soil	No ecological damage caused by this product.

# 337

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

oxygen (7782-44-7)	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Ecology - soil	No ecological damage caused by this product.

Nitrogen (7727-37-9)	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Ecology - soil	No ecological damage caused by this product.

### 12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No known effects from this product.
Effect on the ozone layer	: None.

337	
Effect on the ozone layer	None.
Fluorinated greenhouse gases	False
GWPmix comment	Contains greenhouse gas(es).

hydrogen sulphide (7783-06-4)	
Effect on the ozone layer	No effect on the ozone layer.
Effect on global warming	No known effects from this product.
Fluorinated greenhouse gases	False

carbon monoxide (630-08-0)	
Effect on the ozone layer	No effect on the ozone layer.
Effect on global warming	No known effects from this product.
Fluorinated greenhouse gases	False

Carbon dioxide (124-38-9)	
Effect on the ozone layer	No effect on the ozone layer.
Effect on global warming	When discharged in large quantities may contribute to the greenhouse effect. Contains greenhouse gas(es).
Fluorinated greenhouse gases	False
GWP 100 years	1

oxygen (7782-44-7)	
Effect on the ozone layer	No effect on the ozone layer.
Effect on global warming	None.
Fluorinated greenhouse gases	False

Nitrogen (7727-37-9)	
Effect on the ozone layer	No effect on the ozone layer.
Effect on global warming	None.
Fluorinated greenhouse gases	False

pentane (109-66-0)	
Fluorinated greenhouse gases	False

## SECTION 13: Disposal considerations

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions. Contact supplier if guidance is required. Must not be discharged to atmosphere. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <a href="http://www.eiga.eu">http://www.eiga.eu</a> for more guidance on suitable disposal methods. Return unused product in original container to supplier.
Additional information	: External treatment and disposal of waste should comply with applicable local and/or national regulations.

## SECTION 14: Transport information

14.1. UN number	
UN-No. (ADG)	: 1956
UN-No. (IMDG)	: 1956
UN-No. (IATA)	: 1956

**14.2. Proper Shipping Name - Addition**

<b>Proper Shipping Name (ADG)</b>	: COMPRESSED GAS, N.O.S. (oxygen ; Nitrogen MIXTURE)
<b>Transport by air (ICAO-TI / IATA-DGR)</b>	: Compressed gas, n.o.s. (oxygen ; Nitrogen MIXTURE)
<b>Transport by sea (IMDG)</b>	: COMPRESSED GAS, N.O.S. (oxygen ; Nitrogen MIXTURE)

**14.3. Transport hazard class(es)****ADG**

Transport hazard class(es) (ADG)	: 2.2
Danger labels (ADG)	: 2.2

**IMDG**

Transport hazard class(es) (IMDG)	: 2.2
Danger labels (IMDG)	: 2.2

**IATA**

Transport hazard class(es) (IATA)	: 2.2
Danger labels (IATA)	: 2.2

**14.4. Packing group**

Packing group (ADG)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable

**14.5. Environmental hazards**

Marine pollutant	: No
------------------	------

**14.6. Special precautions for user**

Specific storage requirement	: No data available
Shock sensitivity	: No data available

**14.7. Additional information**

Other information	: No supplementary information available
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

**Transport by road and rail**

UN-No. (ADG)	: 1956
Special provision (ADG)	: 274, 292
Limited quantities (ADG)	: 120ml
Packing instructions (ADG)	: P200

**Transport by sea**

# 337

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

UN-No. (IMDG)	: 1956
Special provisions (IMDG)	: 274, 378
Packing instructions (IMDG)	: P200
EmS-No. (Fire)	: F-C - FIRE SCHEDULE Charlie - NON-FLAMMABLE GASES
EmS-No. (Spillage)	: S-V - SPILLAGE SCHEDULE Victor - GASES (NON-FLAMMABLE, NON-TOXIC)
Stowage category (IMDG)	: A

### Air transport

UN-No. (IATA)	: 1956
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: 200
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 200
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A202
ERG code (IATA)	: 2L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code	: 2TE
--------------	-------

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Abbreviations and acronyms	: ATE - Acute Toxicity Estimate CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 EINECS - European Inventory of Existing Commercial Chemical Substances CAS# - Chemical Abstract Service number PPE - Personal Protection Equipment LC50 - Lethal Concentration to 50 % of a test population RMM - Risk Management Measures PBT - Persistent, Bioaccumulative and Toxic vPvB - Very Persistent and Very Bioaccumulative STOT- SE : Specific Target Organ Toxicity - Single Exposure CSA - Chemical Safety Assessment EN - European Standard UN - United Nations ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road IATA - International Air Transport Association IMDG code - International Maritime Dangerous Goods RID - Regulations concerning the International Carriage of Dangerous Goods by Rail WGK - Water Hazard Class STOT - RE : Specific Target Organ Toxicity - Repeated Exposure
Revision date	: 21/12/2016
Other information	: Classification using data from databases maintained by the European Industrial Gases Association (EIGA). Data is maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at : <a href="http://www.eiga.eu">http://www.eiga.eu</a> . Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP.

Classification:

Press. Gas (Comp.)	H280
--------------------	------

Full text of H-statements:

# 337

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Repr. 1A	Reproductive toxicity, Category 1A
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*